

WPC A6 Wireless Charging Module

Single Coil Version



FEATURES ROHS





- Designed to meet WPC Qi Standard, power transmitter design A6 compliant
- Operating temperature -40° C to $+125^{\circ}$ C
- Assembled with ferrite plate which is built with WPC listed ferrite material, high Q for maximum power transmission

APPLICATIONS

- Wireless charger for general electronic device or aftermarket accessories
- Wireless charger for office, residential or public area application
- Wireless charger for power tools or any other devices that need contactless power
- Wireless charging embedded solution for automobile central console, arm rest...etc

ELECTRICAL SPECIFICATIONS


PART NUMBER	INDUCTANCE ($\mu H \pm 10\%$)			DCR Max	Q @ 100 KHz/1V
	MIN	NOM	MAX	(mΩ)	(MIN)
SWC5547AK120-500	11.25	12.50	13.75	65	90


- Inductance tested at 100KHz,1V
- Operating temperature range: -40°C ~ +125°C (Including self-heating)
- Storage temperature range (packaging conditions): -10°C ~ +40°C and RH 70%(MAX)

SHAPES AND DIMENSIONS

Unit:mm

Α	В	С	D	E	F
45.20±1.00	53.20±1.00	19.50±0.50	27.50±0.50	10.00 Min.	5.00 <u>±</u> 2.00
C		V	D.0	N	
G	п	K	M	N	
1.00 ± 0.10	5.00 Ref.	3.00 Max.	47.20 ± 0.50	55.20 ± 0.50	





PART NUMBER SYSTEM EXAMPLE

	SWC	<u>5547</u>	AK	<u>120</u> -	<u>500</u>
l	Coil Type	Part Size Code	Height Code	Inductance Code	Catalog or Custom Information

USA: +1.423.308.1690 Europe: +42.0.4885.7511.1 Asia: +86.757.2563.8860

MCP-DS-WPC A6 Single REV1.0 0414